HP Latex 800 Printer

Grow with high-value jobs and high-productivity printing—and sharpen your sustainability edge





Win the high-value jobs you are after

- Deliver vivid colors at high speed and get • striking contrast using pure blacks.
- Expect reliable, sharp 4-point text with HP Latex printheads featuring 10-picoliter ink drops.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

Robust, smart, and productive printing

- Drive high productivity with saturated color at speeds up to 36 m²/hr outdoor¹, easy spindleless loading.
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Help reduce running costs with cost-effective 3liter HP ink cartridges, changed while the printer runs.

Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks-no ٠ HAPs², no required hazard warning labels, and odorless prints.³
- Local HP Eco-Carton outer carton recycling.⁴
- Choose from a wide range of compatible ecoconscious media.5
- HP Latex prints are recyclable, returnable, or non-hazardous and safe for disposal.⁶

For more information, please visithttp://www.hp.com/go/latex800series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ Outdoormode (Banner) 4-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects. ² HP Latex hks weretested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected. ³ There is abroad set of mediawith very different todor profiles. Some of the media can affect the odor performance of the final print. ⁴ The ink carrind geouter carton is 100% recyclable through local cardboard/page programs.

⁵ See http://www.hp.com/go/mediasolutionslocator
⁶ Most HP large format paper-based printing materials can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the free, convenient HP Large Format Media take-back programs may not exist in your reas. See http://www.HPLFMedia.com/hp.ecosolutions for details. HP large format printing materials, both unprinted and printed with Original HP Latex hks, are non-hazardous and safe for disposal. Contact your local wastermanagement authority for local area-specific instructions.

Technical specifications Drint

Print	
Printing modes	122 m²/hr - Max Speed (1-pass) 36 m²/hr - High Speed (4-pass) 25 m²/hr - Production Fast (6-pass) 20 m²/hr - Production Quality, Textiles and Backlits (8-pass) 17 m²/hr - High Saturation (12-pass) 14 m²/hr - High Saturation Backlits and Textiles (14-pass) ¹
Printresolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat)
Cartridgesize	3L
Printheads	8 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Long-term print-to-print repeatability	95%ofcolors ≤ 1.5 dE2000 ²
Media	
Handling	Roll feed, take-up reel, wiper roller ³ , media saver, automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper-based media, and film)
Media typ es	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles ⁵
Roll size	419 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Roll weight	55 kg
Roll diameter	250 mm
Thickness	Up to 0.5 mm
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; hdoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (W x D	xH)
Printer	2583 x866 x1402 mm
Shipping	2753x1100x1666mm
Operating area	2793 x 2100 mm
Weight	
Printer	292 kg
Shipping	436 kg
What's in the box	HP Latex800 Printer, printheads, maintenance cartridge, printer stand, take-up reel, medialoading accessory, user maintenancekit, edgeholders, quick reference guide, documentation software, power cords, air purges, 2-in spinle adaptor
Environmental rang	
Operating temperature	15 to 30°C
Operating humidity	20 to 80%RH (non-condensing)
Acoustics	
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)
Power	
Consumption	1.8-2.8 kW (5 kW peak) (printing), 105 W (ready)
	1.8-2.8 kW (5 kW peak) (printing), 105 W (ready) hput voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord
Requirements	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A
Requirements Certification	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A
Requirements Certification Safety	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord max per power cord EC 60950-1+A1+A2 compliant; EC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN
Consumption Requirements Certification Safety Electromagnetic Environmental	Input voltage (auto ranging) 200-240 V two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord EC 60950-1 * A1 * A2 compliant; EC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China(CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada ((CES), EU (EMC Directive),

Ordering information

Product	
YOU21A	HP Latex 800 Printer
Accessories	
21V10A 421S3A 7HR16A 7HR18A 7HR19A T7U73A	HP Latex 700/800 User Maintenance Kit HP Latex Media Feed Accessory HP Latex 700/800 Textle Kit Accessory HP Latex 700/800 Ink Collector Foams Kit HP Latex 700/800 Media Loading Accessory HP Latex 500/700/800 Wiper Roller
Original HP	rinting supplies

ng supp

4

Original HP large format printing materials

HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified⁶, FSC® certified⁷, meets AgBB criteria⁸) HP Photo-realistic Poster Paper HP Premium Satin Carvas HP Prime Mate Ari GP (REACH compliant⁸) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant⁹)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U1 3DBE HP 2 year Next Business Day with Defective Media Retention U1 3DDE HP 3 year Next Business Day with Defective Media Retention U1 3DLPE HP 1 year Post Warranty Next Business Day with Defective Media Retention U1 3DRPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

ECO highlights

Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard¹ Can win new business with odortess prints, ULE COLOGOPUL GREENGUARD Gold Certified ink, and more² High-volume - liter MP Eco-Catron ink cartinges—crator based design significantly reduces plastic :

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

¹ Seehttp://www.roadmaptozero.com. Printing with HP Latex Inks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin. ² Thereis a broad set of mediawith very different od or profiles. Some of the media can affect the od or performance of the final print. For certifications, seehttp://www.ul.com/EL and http://www.ul.com/g

Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.
 The color variation between printed jobs has been measured at 12 pass mode on viryl media. Reflective measurements on a 943 color target under CE standard Rluminant D50, and according to the standard CEDE2000 as per CE Draft Standard D514-6/E:2012. S% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results.
 Wiper roller is an optional accessory.
 Automatic horizontal cutter is for use with thinner banners and carvas only. It is recommended to perform atest.
 TextleRKA accessory.
 Catter of Color Certification to UL 2818 demonstrates that products are certified to ULS GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.greenguard.org
 Trademark license conder SC - C115319.
 With HP Latexinks, prints meet AgBB criteria for health -related evaluation of VOC emissions. See http://unweitbundesamt.dee/ntopics/health.cmissions-working-groups/committee-for-health-related-evaluation-of-building
 This product does not contain substances listed as SVHC (155) per Annex XIV of the EUREACH directive published as of June 16, 2014 in concentration seckeding 0.1%. To determine the status of SVHC ht P products, see the MP REACH Declaration published at HP Printing Products and Consumable Supplies.



